



# Test Report: LPC-100-2100

---

100W Single Output LED Power Supply

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST

Environment Test

## DESIGN VERIFY TEST


### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CURRENT ACCURACY	< $\pm 5\%$	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	TEST: 2.1 %
2	CONSTANT CURRENT REGION	V1: 24 V~ 48 V	I/P: 230VAC O/P: LED MODE Ta:25°C	V1: 14.85 V~ 47.85 V
3	RIPPLE CURRENT	< $\pm 5\%$	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	TEST: 3.89%
4	LINE REGULATION	V1: -1 %~ 1 %	I/P: 100VAC~ 264VAC O/P: FULL LOAD Ta: 25°C	V1: -0 %~ 0 %
5	OUTPUT VOLTAGE TOLERANCE	V1: -1.5 %~ 1.5 %	I/P: 100VAC /264VAC O/P: FULL/ MIN LOAD Ta: 25°C	V1: -0.271%~0.083%
6	OVER/UNDERSHOOT TEST	< $\pm 5\%$	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	< 5 %
7	RIPPLE & NOISE(Max)	V1: 1.0Vp-p	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	V1: 48.8mVp-p
<p>high frequency :</p> <p>Ch1 Pk-Pk 48.4mV</p>		<p>low frequency :</p> <p>Ch1 Pk-Pk 48.8mV</p>		
8	SET UP TIME(Max)	230VAC/ 1000ms 115VAC/ 2000ms	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	230VAC/ 572 ms 115VAC/ 1210 ms



100W Single Output LED Power Supply

LPC-100 series





INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~264VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	87V~267V
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+15%=300 V O/P: FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230Vac ON: 0.5 Sec OFF: 0.5 Sec 20MIN (3)230Vac ON: 3Sec OFF: 3Sec 12HOURS ( POWER ON/OFF NO DAMAGE )	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~264 VAC O/P: FULL~MIN LOAD Ta: 25°C	TEST: OK
3	INPUT CURRENT (Typ)	230V/ 1.2A 115V/ 2.2A	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I =1.05A/ 230VAC I =1.72A/ 115VAC
4	LEAKAGE CURRENT	< 0.25mA / 240 VAC	I/P: 240 VAC O/P: Min LOAD Ta: 25°C	L-FG: 0.003 mA N-FG: 0.003 mA
5	INRUSH CURRENT(Typ)	230V/ 75A Twidth =980 us measured at 50% Ipeak COLD START	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	I = 51.4A Twidth =864us
<p>INPUT=230VAC/50HZ @ FULL LOAD</p> <p>CH1 : Input current CH2 : AC Input Voltage</p> <p>Ch1 100 V 10.0 A 400µs Ch2 30.0 A</p> <p>Δ: 1.20 A @: 25.6 A Δ: 864µs @: 856µs</p> <p>Ch2 Max 51.4 A</p> <p>39.80 %</p>				
6	EFFICIENCY(Typ)	89%	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	90.16%



## PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER VOLTAGE PROTECTION	V1: 58 V~ 68 V	I/P: 90VAC I/P: 230VAC I/P: 264VAC O/P: TESTING Ta: 25°C	62.08V/ 90VAC 62.04V/ 230VAC 62.13V/ 264VAC Shut down o/p voltage, re-power on to recover
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant current limiting, recovers automatically after fault condition is removed


## COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated 700V/11A	I/P: High-Line +3V =267V O/P: (1)Full Load Turn on (2)Output Short (3)Full load continue Ta: 25°C	(1) 606V (2) 482V (3) 578V
2	Diode Peak Voltage	D102 Rated 400V/10A	I/P: High-Line +3V =267V O/P: (1)Full Load Turn on (2)Output Short (3)Full load continue Ta: 25°C	(1) 198V (2) 218V (3) 189V
3	Input Capacitor Voltage	C5 Rated 100uF/ 400V	I/P: High-Line +3V =267 V O/P: (1)Full Load input on/off (2) Min load input on /Off Ta: 25°C	(1) 396V (2) 372V
4	Control IC Voltage Test	U1 Rated 28V (MAX.)	I/P: High-Line +3V =267 V O/P: (1)Full Load input on/off (2) Min load input on /Off Ta: 25°C	(1) 17.2V (2) 17.2V

## SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3KVAC/min	I/P-O/P: 3.6 KVAC/min Ta: 25°C	I/P-O/P: 2.44mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P: 500VDC>100MΩ	I/P-O/P: 500 VDC Ta: 25°C	I/P-O/P: >9999MΩ NO DAMAGE

## E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P: ≤80% LOAD Ta: 25°C	PASS
				
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N : 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
7	Test by certified Lab & Test Report Prepare			

## RELIABILITY TEST

### ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																												
1	TEMPERATURE RISE TEST	MODEL: LPC-100-2100 1. ROOM AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 21.9 °C 2. HIGH AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 54.2 °C																																																														
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 21.9 °C</th> <th>HIGH AMBIENT Ta= 54.2 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF3</td><td>50.9°C</td><td>76.3°C</td></tr> <tr><td>2</td><td>C6</td><td>55.0°C</td><td>80.9°C</td></tr> <tr><td>3</td><td>Q1</td><td>62.0°C</td><td>90.3°C</td></tr> <tr><td>4</td><td>D2</td><td>62.0°C</td><td>90.9°C</td></tr> <tr><td>5</td><td>C26</td><td>56.8°C</td><td>84.6°C</td></tr> <tr><td>6</td><td>R9</td><td>68.6°C</td><td>96.0°C</td></tr> <tr><td>7</td><td>U1</td><td>52.4°C</td><td>80.7°C</td></tr> <tr><td>8</td><td>T1</td><td>70.9°C</td><td>98.3°C</td></tr> <tr><td>9</td><td>D102</td><td>68.0°C</td><td>95.1°C</td></tr> <tr><td>10</td><td>C120</td><td>54.8°C</td><td>82.8°C</td></tr> <tr><td>11</td><td>C106</td><td>62.4°C</td><td>89.5°C</td></tr> <tr><td>12</td><td>C105</td><td>58.9°C</td><td>86.2°C</td></tr> <tr><td>13</td><td>RTH2</td><td>55.7°C</td><td>83.5°C</td></tr> <tr><td>14</td><td>Tc</td><td>48.8°C</td><td>76.8°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 21.9 °C	HIGH AMBIENT Ta= 54.2 °C	1	LF3	50.9°C	76.3°C	2	C6	55.0°C	80.9°C	3	Q1	62.0°C	90.3°C	4	D2	62.0°C	90.9°C	5	C26	56.8°C	84.6°C	6	R9	68.6°C	96.0°C	7	U1	52.4°C	80.7°C	8	T1	70.9°C	98.3°C	9	D102	68.0°C	95.1°C	10	C120	54.8°C	82.8°C	11	C106	62.4°C	89.5°C	12	C105	58.9°C	86.2°C	13	RTH2	55.7°C	83.5°C	14	Tc	48.8°C	76.8°C
NO	Position	ROOM AMBIENT Ta= 21.9 °C	HIGH AMBIENT Ta= 54.2 °C																																																													
1	LF3	50.9°C	76.3°C																																																													
2	C6	55.0°C	80.9°C																																																													
3	Q1	62.0°C	90.3°C																																																													
4	D2	62.0°C	90.9°C																																																													
5	C26	56.8°C	84.6°C																																																													
6	R9	68.6°C	96.0°C																																																													
7	U1	52.4°C	80.7°C																																																													
8	T1	70.9°C	98.3°C																																																													
9	D102	68.0°C	95.1°C																																																													
10	C120	54.8°C	82.8°C																																																													
11	C106	62.4°C	89.5°C																																																													
12	C105	58.9°C	86.2°C																																																													
13	RTH2	55.7°C	83.5°C																																																													
14	Tc	48.8°C	76.8°C																																																													
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 264VAC/100VAC O/P: 100 % LOAD Ta= -30 °C	TEST: OK																																																												
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P: 272 VAC O/P: FULL LOAD Ta= 50 °C HUMIDITY= 95 % R.H	TEST: OK																																																												
4	TEMPERATURE COEFFICIENT	±0.03 %/°C (0~50°C)	I/P: 230 VAC O/P: FULL LOAD	±0.013 %/°C (0~50°C)																																																												
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature: -45°C~+90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 5 CYCLE 5. Input/Output condition: STATIC		TEST: OK																																																												
6	THERMAL SHOCK TEST	1. Thermal shock Temperature: -30°C~+55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 10 CYCLE 5. Input/Output condition: 230VAC/Full Load AC ON/OFF TEST turn on 58 sec; turn off 2 sec		TEST: OK																																																												



100W Single Output LED Power Supply

LPC-100 series

7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency: 10~500Hz (3) Sweep Time: 10min/sweep cycle (4) Acceleration: 3G (5) Test Time: 90min in each axis (X.Y.Z) (6) Ta: 25°C	TEST: OK
8	CAPACITOR LIFE CYCLE	LPC-100-2100 : SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P: 230VAC O/P: FULL LOAD Ta= 25 °C LIFE TIME (2) I/P: 230VAC O/P: FULL LOAD Ta= 50 °C LIFE TIME (3) I/P: 230VAC O/P: 75% LOAD Ta= 50 °C LIFE TIME (4) I/P: 230VAC O/P: 50% LOAD Ta= 50 °C LIFE TIME	(1) 146929.5 HRS (2) 37279.2 HRS (3) 49832.4 HRS (4) 61339.5 HRS
9	MTBF	MIL-HDBK-217F TOTAL FAILURE RATE: 511K HRS	
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 20,000 hours @ Tcase 75°C	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	ZHANGZJ/ZHUOKB	SKY	LIUWY